



Catalogue:

CATERING

Chapter:

OVENS

Article:

ACG-061 LPG 230V 1N 50Hz

Code:

19011043

DIMENSIONS AND WEIGHTS

		<u>Net dimension</u>	<u>Packed</u>
Length	mm	898,00	1.001,00
Depth	mm	987,00	980,00
Height	mm	900,00	1.055,00
Weight	kg	125,00	150,00
Volume	m3	0,75	1,04

ELECTRICITY

230V	50Hz	
Power		1,20 kW
Connections	230 V. 1+N+T	2X1,5+T - 10 A
	230 V. III+T	
	400 V. III+N+T	

GAS

Power		12,00 kW
Gas type	LPG	
Consumption		1,27 kg/h
Pressure	LPG G30/G31 28-30/37 mbar	

WATER

Consumption		15 lit/h
Pressure	Water Pres:200-400kPa(2-4bar)	

STEAM

Not necessary

AIR

Not necessary

REFRIGERATION

LEVEL SOUND

62,00 db

CERTIFICATES

DESCRIPTION

ADVANCE CONCEPT INJECTION COMBI OVEN, ACG-061

Technology made simple :

- Affordable
- Easy to use
- Efficient
- Simple
- Perfect results

Capacity for 6 1/1-GN trays.

Stainless steel burner with electronic control system with sparking plug ignition.

Frequency modulation for the convection burner.

Digital push-button controls and two "Scroll" buttons.

5 Cooking methods: Steam, Combi, Regeneration, Delta and Convection (up to 300°C).

Steam generated by injection in the cooking chamber.

Electronic temperature core probe.

Preheating option.

3 Speeds - 2 power ranges.

Cold-Down chamber cooling system.

"Auto-reverse" system to reverse fan rotation.

Error detection system. "Repair service" mode system.

IPX5 Protection.

AUTOMATIC CLEANING - Wash program for the cooking chamber.

Door with double glass and hermetic locking and folding interior glass.

Electrical connection: 230 V - 1+N - 1.2 kW.

Gas heating power: 12 kW.

Dimensions: 898 x 867 x 846 mm.

Accessories in option:

- Support SH-11
- Structure for trays EB-061
- Structure for dishes EP-061
- Trolley CP-11.
- External shower

Connections and diameters

ELECTRICITY	YES
DRAIN	1"
SOFT WATER	3/4
COLD WATER	3/4
GAS	3/4

