



Catalogue :

**SERIE 900 KORE**

Chapter :

**CHARCOALS 900 KORE**

Article :

**B-G9101 LPG 230V 1N**

Code:

**19023959**

<u>DIMENSIONS AND WEIGHTS</u>		<u>Net dimensions</u>	<u>Packed</u>
Length	mm	<b>800,00</b>	<b>1.022,00</b>
Depth	mm	<b>930,00</b>	<b>840,00</b>
Height	mm	<b>850,00</b>	<b>1.265,00</b>
Weight	kg	<b>70,00</b>	<b>90,00</b>
Volume	m3	<b>0,69</b>	<b>1,09</b>
<u>ELECTRICITY</u>		<b>230V</b>	<b>50/60Hz</b>
	Power		<b>0,10 kW</b>
Connections	230 V. 1+N+T	<b>2X1,5+T</b>	
	230 V. III+T		
	400 V. III+N+T		
<u>GAS</u>	Power		<b>22,00 kW</b>
	Gas type	<b>LPG</b>	
	Consumption		<b>1,71 kg/h</b>
	Pressure	<b>LPG G30/G31 28-30/37 mbar</b>	
<u>WATER</u>	Not necessary		
<u>STEAM</u>	Not necessary		
<u>AIR</u>	Not necessary		

DESCRIPTION

**GAS GRILL TOP, B-G9101**  
 The new Fagor industrial grills do not carbonize food surface and provide a healthy cooking.  
 Our grills reach a very high temperature (400°C) that seals the product surface quickly and keeps a more juicy inside .  
 Their new features include steam cooking.  
 2 mm stainless AISI-304 steel top with rounded edges for easy cleaning. Laser cut and automatic welding for a perfect adjustment of sides between modules with square angle finish.  
 Gas heated model with three tubular burners with radiant plates. Independent control for each burner group by means of safety valve with thermocouple. Electronic ignition.  
 Cast iron grill with four 170 mm wide sections. Easy to remove without tools for any easy cleaning.  
 Reversible grill to cook different products in a different way:  
 \_ Grooved side and slanted grill for meat.  
 \_ Smooth flat horizontal side for fish and vegetables  
 Food gets cooked and grilled from direct contact and heat irradiation from underneath burners.  
 Grill surface 48 dm2  
 Fitted with two cooking fat drainage holes at the front to collect fat and grease from cooking, and 12 litre collecting trays at the bottom. Fat collecting trays may be filled with water. Thanks to the heat irradiated by the burners a low intensity steam is produced to cook in a steam atmosphere.  
 Removable 130 mm stainless steel anti splash shield, easy to wash.  
 Water-tight and protecting-support controls.  
 High temperature protector for the chimney made of enamelled cast iron.  
 Front access to components.  
 According to European standards for components and panels temperature, efficiencies and combustion, and sanitary regulations (EN-60335 and EN-203)  
 IPX5 grade water protection equipment.  
 Maximum power: 22.0 kW - Gas  
 It requires an 230V - 1+N power supply.  
 Dimensions: 800 x 930 x 850 mm.

SOUND LEVEL < **65,00** db

CERTIFICATES **1312CR6178**

<u>INSTALLATION - CONNECTIONS</u>		<u>Ø</u>
▶	ELECTRICITY	SI
▶	GAS	"R,3/4""G"





Catalogue :  
**SERIE 900 KORE**

Chapter :  
**CHARCOALS 900 KORE**

Article :  
**B-G9101 LPG 230V 1N**

Code :  
**19023959**

**SCHEMA - DIMENSIONS**

