



700 Series

Fryers 700

**GAS FRYER, FG7-05 - 2C**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>350,00</b>	<b>390,00</b>
Depth	mm	<b>775,00</b>	<b>835,00</b>
Height	mm	<b>850,00</b>	<b>1.060,00</b>
Weigth	Kg	<b>57,00</b>	<b>68,00</b>
Volumen	m3	<b>0,23</b>	<b>0,35</b>

**ELECTRICITY**

<u>Electric power</u>		KW	
230V - 1+N			<b>0,05</b>
230V - III			<b>2x1,5+T - 2 A</b>
400V - III+N			

**WATER**

Not used

**GAS**

Power		KW	<b>15,00</b>
		Kcal/h	<b>12.900,00</b>
LPG		Consumption (kg/h)	<b>1,25</b>
		Pressure (g/cm2)	<b>37,00</b>
Natural Gas		Consumption (m3/h)	<b>1,59</b>
		Pressure (g/cm2)	<b>18,00</b>

**STEAM**

Not used

**AIR**

Not used

GAS FRYER, FG7-05 - 2C

Made of stainless steel

Capacity: one 15 litre oil/well.

Tank equipment: 2 small baskets 250x135 mm .

Cast iron burners.

Thermostat temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple.

Safety thermostat.

Drainage tap.

Power: 15 kW.

Electrical connection 230 V - 1+N+T.

Dimensions: 350 x 775 x 850 mm.

**Certificate EQNET- CE**

**Cgaz-1312BT5118**

<b>Connections points</b>	<b>X</b>	<b>Y</b>	<b>Z</b>	<b>Diameter</b>	<b>Information</b>
ELECTRICITY	286	540	150		Prever Interruptor diferencial
GAS	312	492	105	R.3/4"G	Prever regulador y llave de corte individual

