



700 Series

Fryers 700

GAS FRYER, FG7-10 - 2C

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	742,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	104,00	119,00
Volumen	m3	0,46	0,66

ELECTRICITY

<u>Electric power</u>		KW	
230V - 1+N			0,05
230V - III			2x1,5+T - 2 A
400V - III+N			

WATER

Not used

GAS

Power		KW	30,00
		Kcal/h	25.800,00
LPG	Consumption (kg/h)		2,50
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		3,18
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS FRYER, FG7-10 - 2C

Made of stainless steel

Capacity: two 15 litre oil/well.

Tank equipment: 1 basket 250x280 mm by tank.

Cast iron burners.

Thermostats temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple.

Safety thermostat.

Drainage taps.

Power: 30 kW.

Electrical connection 230 V - 1+N+T.

Dimensions: 700 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5118

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	286	540	150		Prever Interruptor diferencial
ELECTRICITY	636	540	150		Prever Interruptor diferencial
GAS	662	492	105	R.3/4"G	Prever regulador y llave de corte individual
GAS	312	492	105	R.3/4"G	Prever regulador y llave de corte individual

