



700 Series

Fryers 700

**GAS FRYER, FG7-10 - 4C**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>700,00</b>	<b>742,00</b>
Depth	mm	<b>775,00</b>	<b>835,00</b>
Height	mm	<b>850,00</b>	<b>1.060,00</b>
Weigth	Kg	<b>104,00</b>	<b>119,00</b>
Volumen	m3	<b>0,46</b>	<b>0,66</b>

**ELECTRICITY**

<u>Electric power</u>		KW	
230V - 1+N			<b>0,05</b>
230V - III			<b>2x1,5+T - 2 A</b>
400V - III+N			

**WATER**

Not used

**GAS**

Power		KW	<b>30,00</b>
		Kcal/h	<b>25.800,00</b>
LPG	Consumption (kg/h)		<b>2,50</b>
	Pressure (g/cm2)		<b>37,00</b>
Natural Gas	Consumption (m3/h)		<b>3,18</b>
	Pressure (g/cm2)		<b>18,00</b>

**STEAM**

Not used

**AIR**

Not used

GAS FRYER, FG7-10 - 4C

Made of stainless steel

Capacity: two 15 litre oil/well.

Tank equipment: 2 baskets 250x135 mm by tank.

Cast iron burners.

Thermostats temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple.

Safety thermostat.

Drainage taps.

Power: 30 kW.

Electrical connection 230 V - 1+N+T.

Dimensions: 700 x 775 x 850 mm.

**Certificate EQNET- CE**

**Cgaz-1312BT5118**

<b>Connections points</b>	<b>X</b>	<b>Y</b>	<b>Z</b>	<b>Diameter</b>	<b>Information</b>
ELECTRICITY	286	540	150		Prever Interruptor diferencial
ELECTRICITY	636	540	150		Prever Interruptor diferencial
GAS	662	492	105	R.3/4"G	Prever regulador y llave de corte individual
GAS	312	492	105	R.3/4"G	Prever regulador y llave de corte individual

