



## Dishwashing

### Conveyor dishwashers

## DISHWASHER, FI-200 D

### DIMENSIONS

		Article	Packed
Length	mm	1.430,00	1.530,00
Depth	mm	780,00	960,00
Height	mm	1.580,00	1.900,00
Weigth	Kg	211,00	305,00
Volumen	m3	1,76	2,79

### ELECTRICITY

Electric power	KW	
230V -1+N		37,38
230V - III		3x25+T - 100 A
400V - III+N		4x16+T - 63 A

### WATER

Water consumption (lit/h)	450,00
Pressure (Kg/cm2)	2 - 4

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### LEVEL SOUND

(dB) 72,00

### Certificate EQNET- CE

SGS-2199-0192-1

### DISHWASHER, FI-200 D

Made of stainless steel.  
 Entry on the right side.  
 Two conveyor speeds:  
 1st. Speed: 85 baskets/h.  
 2nd. Speed: 110 baskets/h.  
 Splash-guard module at entry.  
 Dividing curtains highly resistant to chemical agents and heat.  
 Wash tank for 45 litres.  
 Tray-filters removable for cleaning.  
 Two wash-pumps, 600 W each.  
 Tank heated by means of shielded elements, 9 kW.  
 Thermostatically adjusted (wash temperature: 60 °C).  
 Built-in rinse water boiler (27 kW).  
 Safety thermostat.  
 Analogic thermometers for wash and rinse water temperature.  
 Water consumption: 450 l/h.  
 Magnetic switches for wash, rinse and door opening.  
 Energy economiser system.  
 Motor-reducer: 180 W.  
 Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105 and 10 cutlery containers.  
 Power: 37.38 kW.  
 Dimensions: 1430 x 780 x 1580 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	70	160	320		Prever Interruptor diferencial
SOFT HOT WATER	380	630	240	3/4"	Prever llave de corte en la toma
DRAIN	810	440	130	38	

