



Dishwashing

Conveyor dishwashers

DISHWASHER, FI-200 I

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.430,00	1.530,00
Depth	mm	780,00	960,00
Height	mm	1.580,00	1.900,00
Weigth	Kg	211,00	305,00
Volumen	m3	1,76	2,79

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		
230V - III		3x25+T - 100 A
400V - III+N		4x16+T - 63 A

WATER

Water consumption (lit/h)	450,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 72,00

Certificate EQNET- CE

SGS-2199-0192-1

DISHWASHER, FI-200 I

Made of stainless steel.

Entry on the left side.

Two conveyor speeds:

1st. Speed: 85 baskets/h.

2nd. Speed: 110 baskets/h.

Splash-guard module at entry.

Dividing curtains highly resistant to chemical agents and heat.

Wash tank for 45 litres.

Tray-filters removable for cleaning.

Two wash-pumps, 600 W each.

Tank heated by means of shielded elements, 9 kW.

Thermostatically adjusted (wash temperature: 60 °C).

Built-in rinse water boiler (27 kW).

Safety thermostat.

Analogic thermometers for wash and rinse water temperature.

Water consumption: 450 l/h.

Magnetic switches for wash, rinse and door opening.

Energy economiser system.

Motor-reducer: 180 W.

Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105 and 10 cutlery containers.

Power: 37.38 kW.

Dimensions: 1430 x 780 x 1580 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	70	160	320		Prever Interruptor diferencial
DRAIN	810	440	130	38	
SOFT HOT WATER	380	630	240	3/4"	Prever llave de corte en la toma

