



Dishwashing

Conveyor dishwashers

CONVEYOR DISHWASHER, FI-280 I

DIMENSIONS

		Article	Packed
Length	mm	1.750,00	1.850,00
Depth	mm	780,00	955,00
Height	mm	1.580,00	1.890,00
Weigth	Kg	259,00	382,00
Volumen	m3	2,16	3,34

ELECTRICITY

Electric power	KW	
230V -1+N		
230V - III		3x50+T - 160 A
400V - III+N		4x25+T - 100 A

WATER

Water consumption (lit/h)	360,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 72,00

CONVEYOR DISHWASHER, FI-280 I

Made of stainless steel.

Entry on the left side.

Two conveyor speeds:

-1st. Speed: 103 baskets/h.

-2nd. Speed: 155 baskets/h.

Splash-guard module at entry.

Wash module and double rinse module.

Dividing curtains highly resistant to chemical agents and heat.

Wash tank 90 litres. Tray-filters removable for cleaning.

Wash pump 2.2 kW. Tank heated by means of shielded elements, 12 kW.

Thermostatically adjusted (wash temperature: 60 °C).

Pre-rinse module. Tank heated by means of shielded elements, 5 kW.

Built-in rinse water boiler (27 kW).

Safety thermostat.

Analogic thermometers for wash and rinse water temperature.

Water consumption: 360 l/h.

Magnetic switches for wash, rinse and door opening.

Energy economiser system.

Motor-reducer: 250 W.

Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105, and 16 cutlery containers.

Power: 46.2 kW.

Dimensions: 1750 x 780 x 1580 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	700	50	1.440		Prever Interruptor diferencial
SOFT HOT WATER	680	630	240	3/4"	Prever llave de corte en la toma
DRAIN	1.200	425	130	38	

