



Dishwashing

Conveyor dishwashers

CONVEYOR DISHWASHER, FI-370 I

DIMENSIONS

		Article	Packed
Length	mm	2.350,00	2.440,00
Depth	mm	780,00	955,00
Height	mm	1.580,00	1.890,00
Weigth	Kg	381,00	556,00
Volumen	m3	2,90	4,40

ELECTRICITY

Electric power	KW	
230V -1+N		47,40
230V - III		3x50+T - 160 A
400V - III+N		4x25+T - 100 A

WATER

Water consumption (lit/h)	360,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 72,00

CONVEYOR DISHWASHER, FI-370 I

Made of stainless steel.
 Entry on the left side.
 Two conveyor speeds:
 1st. Speed: 137 baskets/h.
 2nd. Speed: 205 baskets/h.
 Splash-guard module at entry.
 Dividing curtains highly resistant to chemical agents and heat.
 Prewashing module:
 -Tank 55 litres
 -2 pumps x 0.6 kW.
 -No heating.
 Washing module:
 -Tank 90 litres.
 -Pump: 2.2 kW.
 -Heating power: 12 kW.
 Double rinse module:
 -Pre-rinse module
 -Heating power: 5 kW.
 Rinse water boiler (27 kW). Safety thermostat.
 Analogic thermometers for wash and rinse water temperature.
 Tray-filters removable for cleaning.
 Thermostatically adjusted: wash 60 °C, and rinse 90 °C.
 Safety thermostat.
 Analogic thermometers for wash and rinse water temperature.
 Water consumption: 360 l/h.
 Magnetic switches for wash, rinse and door opening.
 Energy economiser system.
 Motor-reducer: 250 W.
 Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105, and 16 cutlery containers.
 Electrical power: 47.4 kW.
 Dimensions: 2.350 x 780 x 1.580 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	700	50	1.440		Prever Interruptor diferencial
SOFT HOT WATER	680	630	240	3/4"	Prever llave de corte en la toma
DRAIN	1.925	465	130	38	
DRAIN	1.200	425	130	38	

