



## Dishwashing

### Conveyor dishwashers

## CONVEYOR DISHWASHER, FI-460 I

### DIMENSIONS

		Article	Packed
Length	mm	2.650,00	2.750,00
Depth	mm	780,00	960,00
Height	mm	1.580,00	1.900,00
Weigth	Kg	434,00	628,00
Volumen	m3	3,27	5,02

### ELECTRICITY

Electric power	KW	
230V -1+N		55,90
230V - III		3x70+T - 180 A
400V - III+N		4x35+T - 125 A

### WATER

Water consumption (lit/h)	450,00
Pressure (Kg/cm2)	2 - 4

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### LEVEL SOUND

(dB) 72,00

### CONVEYOR DISHWASHER, FI-460 I

Made of stainless steel.  
 Entry on the left side.  
 Two conveyor speeds:  
 -1st. Speed: 170 baskets/h.  
 -2nd. Speed: 255 baskets/h.  
 Equipped with 1 GA-40 hot water generator (gas operating).  
 Splash-guard module at entry.  
 Dividing curtains highly resistant to chemical agents and heat.  
 1st washing module:  
 -Tank 90 litres.  
 -Pump: 2.2 kW.  
 -No heating.  
 Washing module:  
 -Tank 90 litres.  
 -Pump: 2.2 kW.  
 -Heating power: 12 kW.  
 Double rinse module:  
 -Pre-rinse module  
 -Heating power: 5 kW.  
 -Rinse pump 0.26 kW.  
 Rinse water boiler (34.5 kW). Safety thermostat.  
 Analogic thermometers for wash and rinse water temperature.  
 Tray-filters removable for cleaning.  
 Thermostatically adjusted: wash 60 °C, and rinse 90 °C.  
 Safety thermostat.  
 Analogic thermometers for wash and rinse water temperature.  
 Water consumption: 450 l/h.  
 Magnetic switches for wash, rinse and door opening.  
 Energy economiser system.  
 Motor-reducer: 250 W.  
 Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105, and 16 cutlery containers.  
 Electric power: 55.9 kW.  
 Dimensions: 2.650 x 780 x 1.580 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	700	50	1.440		Prever Interruptor diferencial
SOFT HOT WATER	680	630	240	3/4"	Prever llave de corte en la toma
DRAIN	2.100	425	130	38	
DRAIN	1.200	425	130	38	

