



Dishwashing

Conveyor dishwashers

CONVEYOR DISHWASHER, FI-550 D

DIMENSIONS

		Article	Packed
Length	mm	3.250,00	3.350,00
Depth	mm	780,00	960,00
Height	mm	1.580,00	1.900,00
Weigth	Kg	556,00	792,00
Volumen	m3	4,01	6,11

ELECTRICITY

Electric power	KW	
230V -1+N		63,10
230V - III		3x95+T - 200 A
400V - III+N		4x50+T - 125 A

WATER

Water consumption (lit/h)	450,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 72,00

CONVEYOR DISHWASHER, FI-550 D

Made of stainless steel.
 Entry on the right side.
 Two conveyor speeds:
 -1st. Speed: 203 baskets/h.
 -2nd. Speed: 305 baskets/h.
 Splash-guard module at entry.
 Dividing curtains highly resistant to chemical agents and heat.
 Prewashing module:
 -Tank 55 litres
 -2 pumps x 0.6 kW.
 -No heating.
 2nd washing module:
 -Tank 90 litres.
 -Pump: 2.2 kW.
 -Heating power: 6 kW.
 Washing module:
 -Tank 90 litres.
 -Pump: 2.2 kW.
 -Heating power: 12 kW.
 Double rinse module:
 -Pre-rinse module
 -Heating power: 5 kW.
 - Rinse pump 0.26 kW.
 Rinse water boiler (34.5 kW). Safety thermostat.
 Analogic thermometers for wash and rinse water temperature.
 Tray-filters removable for cleaning.
 Thermostatically adjusted: wash 60 °C, and rinse 90 °C.
 Safety thermostat.
 Analogic thermometers for wash and rinse water temperature.
 Water consumption: 450 l/h.
 Magnetic switches for wash, rinse and door opening.
 Energy economiser system.
 Motor-reducer: 250 W.
 Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105, and 16 cutlery containers.
 Electric power: 63.1 kW.
 Dimensions: 3.250 x 780 x 1.580 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	1.850	50	1.440		Prever Interruptor diferencial
DRAIN	675	465	130	38	
DRAIN	1.450	425	130	38	
DRAIN	2.350	425	130	38	
SOFT HOT WATER	1.830	630	240	3/4"	Prever llave de corte en la toma

