



Dishwashing

Conveyor dishwashers

CONVEYOR DISHWASHER, FI-550 I

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	3.250,00	3.350,00
Depth	mm	780,00	960,00
Height	mm	1.580,00	1.900,00
Weigth	Kg	556,00	792,00
Volumen	m3	4,01	6,11

ELECTRICITY

<u>Electric power</u>	KW	63,10
230V - I+N		
230V - III	3x95+T - 200 A	
400V - III+N	4x50+T - 125 A	

WATER

Water consumption (lit/h)	450,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 72,00

CONVEYOR DISHWASHER, FI-550 I

Made of stainless steel.
Entry on the left side.
Two conveyor speeds:
-1st. Speed: 203 baskets/h.
-2nd. Speed: 305 baskets/h.
Splash-guard module at entry.
Dividing curtains highly resistant to chemical agents and heat.
Prewashing module:
-Tank 55 litres
-2 pumps x 0.6 kW.
-No heating.
2nd washing module:
-Tank 90 litres.
-Pump: 2.2 kW.
-Heating power: 6 kW.
Washing module:
-Tank 90 litres.
-Pump: 2.2 kW.
-Heating power: 12 kW.
Double rinse module:
-Pre-rinse module
-Heating power: 5 kW.
- Rinse pump 0.26 kW.
Rinse water boiler (34.5 kW). Safety thermostat.
Analogic thermometers for wash and rinse water temperature.
Tray-filters removable for cleaning.
Thermostatically adjusted: wash 60 °C, and rinse 90 °C.
Safety thermostat.
Analogic thermometers for wash and rinse water temperature.
Water consumption: 450 l/h.
Magnetic switches for wash, rinse and door opening.
Energy economiser system.
Motor-reducer: 250 W.
Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105, and 16 cutlery containers.
Electric power: 63.1 kW.
Dimensions: 3.250 x 780 x 1.580 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	700	50	1.440		Prever Interruptor diferencial
DRAIN	2.825	465	130	38	
DRAIN	1.200	425	130	38	
SOFT HOT WATER	680	630	240	3/4"	Prever llave de corte en la toma
DRAIN	2.100	425	130	38	

