


Distribution and food display - Trolleys - Refrigerated Trolleys -

Model: CF-20

Technical features

Reference	External dimensions (mm)	N sliding guides GN 2/1 (distance 60 mm)	N of pairs of sliding guides GN 2/1	N of plasticized shelves GN 2/1	Freezer power (W)	Туре
19022183	799 x 876 x 1878	17	5	5	550	GN 2/1





Packaging dimensions:

Depth: 860,000 MM

Width: 900,000 MM

Heigth: 1.990,000 MM

Gross weight: 140,000 KG

General features

Especially designed for mainteining and serving previously prepared cold food. Ideal to replace cold chambers or refrigeration units.

Refrigeration unit with fan built inside the chamber. A constant flow of chilled air is generated by the evaporation fans, leading to a fastest temperature drop, as well as a better, more uniform cool air distribution.

Digital reading electronic to monitor and control chamber temperature and defrosting cycle.

Operating temperature ranges from +2° to +8° C with a 32° C room temperature.

Doubled wall with an injected CFC-free, ecological polyurethane 40 Kg/ density isolation. With its highly-insulated walls, heat transfers are reduced thus obtaining energy savings.

Automatic locking mechanism in hinges: when door is in a position of less than a 90° angle it gets fully closed, thus avoiding rising of temperature.

Four (4) sound-proof castors of 125 mm diameter, two of them with brakes for an easy handling and safer use. Non-marking, special rubber bumpers to protect against direct impacts in all four (4) corners.

Key locked door.

Made of stainless steel.

GN 2/1 rod shelves supplied as standard depending on model: five (5) units (CF-20), ten (10) units (CF-40).

Operating voltage and frequency: 230 V/1/50-60 Hz.



